


SA-60D School Digital Amplifier




School Digital Amplifier - SA-60D

Your simple and cost effective solution to achieve clear sound quality in the classroom. This 60W Class D digtal amplifier is designed specially for classroom, training room applications in schools. Paired up with 1-2 speakers, a microphone system, an external audio device or MP3 player and you are already set up. An added advantage for this School Digital Amplifier is that it can be wall-mounted or left on the desk.









School Digital Amplifier SA-60D

Model	SA-60D
Power Source	220 – 240 V AC, 50/60 Hz
Rated Output	60 W
Power Consumption	100 W (rated output), 18 W (EN60065)
Frequency Response	20 Hz – 20 kHz
Distortion	1 % or less
Input	MIC 1, 2: -52 dB*, 600 Ω , unbalanced, ø6.3 phone jack (2P) AUX 1, 2: -20 dB*, 10 k Ω , unbalanced, RCA pin jack
Output	Speaker out: Low impedance (2 x 8 Ω or 1 x 4 Ω), Push-in terminal
Protection	Power Supply Thermal Shut down Power Amplifier Thermal Shut down Power Amplifier Over Current Each protection will be restored automatically
S/N Ratio	MIC 1, 2: 60 dB or more AUX 1, 2: 70 dB or more
Indicator	Power LED (Blue)
Operating Temperature	0 °C to +40 °C
Operating Humidity	90 %RH or less (no condensation)
Finish	Case: Steel plate, off-white, paint / Knob: ABS resin, black
Dimensions (W x H x D)	210 × 70.6 × 180 mm
Weight	1.6 kg
Accessory	Wall mounting pattern paper x 1





Universal Box Speakers BS-1030B / BS-1030W



The box speaker with elegant softline design that fits into modern architecture.

BS-1030B / BS-1030W

• Available in black and white •2-way bass-reflex speaker • Various installation options • Cost-effective high power PA box speaker • Low/ High impedance selectable by rotary switch • Splashproof construction in compliance with IPX4

Infrared Wireless Microphone System IR-700 series



TOA's Infrared Wireless Classroom System incorporates a range of conference and communication enhancing features.

IR-702T Infrared Wireless Tuner

•Built-in 2-channel fixed frequency tuner •Use with up to 4 infrared light receivers •Two line outputs, one with a MIX output switch allowing output of mixed voice from channels A and B

IR-510R Infrared Wireless Receiver

- Infrared wireless receiver designed for exclusive use with IR-702T
- ·Power indicator LED ·Can be mounted to ceiling

IR-300M Infrared Wireless Microphone

- Hands-free microphone with ready-to-wear neck strap Built-in condenser microphone Antibacterial treatment Low-battery indicator
- •2 selectable channels •Infrared light emission intensity adjustable

IR-200M Infrared Wireless Microphone

•Electret condenser microphone unit •Antibacterial treatment •Stable voice transmission •Low-battery indicator •Lightweight •2 selectable channels •Infrared light emission intensity adjustable

Wired Microphones DM series



Like us on Facebook

facebook.com/TOAasiapacific

TOA's Dynamic Wired Microphones are designed with superior voice clarity for speech applications ensuring optimal intelligibility.

DM-270 / DM-320 / DM-420 / DM-520

- •Dynamic, undirectional microphones •Short type slide on/off switch reduces handling noise •XLR-connector with up to 7.5m cable
- Microphone holder included

